



2023 PIONEER 500 SPECIFICATIONS*

ENGINE	
Engine Type	475cc liquid-cooled single-cylinder four-stroke
Bore And Stroke	92.0mm x 71.5mm
Compression Ratio	9.5:1
Valve Train	OHV; two valves per cylinder
Induction	Electronic fuel injection (PGM-FI); 36mm throttle body
DRIVE TRAIN	
Clutch	Automatic
Transmission	Five-speed automatic transmission with AT/MT modes and reverse; paddle shifting; two drive modes include 2WD and 4WD
Driveline	Direct front and rear driveshafts
CHASSIS SUSPENSION BRAKES	
Front Suspension	Independent double-wishbone; 5.8-inch travel
Rear Suspension	Independent double-wishbone with preload adjustability; 5.9-inch travel
Front Brake	Dual 200mm hydraulic discs
Rear Brake	Single 170mm hydraulic disc
Front Tires	24 x 8-12
Rear Tires	24 x 10-12
DIMENSIONS	
Length	102.6 inches
Width	50.0 inches
Height	71.2 inches
Wheelbase	73.0 inches
Bed Capacity	450 pounds
Towing Capacity	1000 pounds
Ground Clearance	8.5 inches
Turning Radius	12.8 feet
Curb Weight	1027 pounds - Includes all standard equipment, required fluids and full tank of fuel.
Fuel Capacity	4.1 gallons, including 1.1-gallon reserve
OTHER	
Safety	Recommended for Drivers 16 years of age and older.
Available Colors	Avenger Red, Black Forest Green
Model ID	SXS500M2
FACTORY WARRANTY INFORMATION	
One Year Included	Transferable, limited warranty
Optional Extended	Extended coverage available with a HondaCare® Protection Plan

*All figures are preliminary and subject to change.

©2024 American Honda Motor Co., Inc. – Powersports Division